

Uninterrupted and accurate monitoring of water turbidity is vital in maintaining optimal operational efficiency and mitigating environmental risks in remote industrial water treatment units.

#### **CHALLENGE**

Industrial water treatment units located in remote areas pose a significant challenge when it comes to monitoring turbidity. Traditional monitoring methods often require on-site personnel and can struggle to provide timely and accurate data due to physical barriers, weather conditions, and other logistical issues. This can result in reduced water quality control, higher operational costs, and potential environmental hazards.

#### **SOLUTION**

The 10Sorex battery-operated Turbidity Sensor, integrating NB-IoT technology, provides an innovative solution to this challenge. With this sensor, companies can receive near real-time turbidity data, regardless of the remoteness of the site. It provides the following benefits:

- **Uninterrupted Monitoring:** The battery-operated sensor enables consistent data transmission, ensuring near real-time turbidity measurements.
- **Robustness:** 10Sorex sensors, with an IP65 rating, are ruggedized and built to withstand harsh industrial applications, promising reliability in diverse conditions.
- **Cost-effective:** This solution eliminates the need for on-site personnel, reducing operational costs significantly.



### **Turbidity Monitoring in Remote Industrial** Water Treatment Units

- Environmental Safeguard: Accurate and timely turbidity data help companies prevent environmental hazards by immediately addressing any water quality issues.
- Efficient Data Transmission: The use of NB-IoT technology ensures reliable data transmission even in areas with poor connectivity.

This solution ensures accurate and timely monitoring of water turbidity, enhancing the operational efficiency of remote industrial water treatment units, and reducing the potential environmental impact.













Battery Operated Ruggedized Design

Easy Install

Pre-Configured

Secure

Quick ROI

#### **TECHNOLOGY**

10Sorex employs cutting-edge communication technology by utilizing the LTE Cat M1 protocol, which operates on 4G and 5G cellular networks, making it suitable for mobile and stationary monitoring applications. However, its remarkably low power consumption and superior penetration rate, specifically designed for industrial solutions, sets it apart. Narrowband Internet of Things (NB-IoT) and LTE Cat M1 are advanced communication technologies that offer significant advantages for monitoring applications. These technologies provide efficient and reliable connectivity for IoT devices, allowing for seamless communication between our sensor and remote monitoring systems. NB-IoT and LTE Cat M1 are known for their low power consumption, enabling prolonged battery life for the devices, which is crucial for remote or hard-to-reach areas. Moreover, these technologies offer excellent penetration capabilities,



allowing for reliable communication even in challenging environments, such as underground or remote locations where devices are often deployed. NB-IoT and LTE Cat M1 also provide secure and scalable connectivity, enabling robust and cost-effective solutions for monitoring applications in various industrial sectors, including agriculture, utilities, logistics, and more.



# Turbidity Monitoring in Remote Industrial Water Treatment Units

#### **SENSOR TECHNICAL SPECIFICATIONS**

•	Measurement principle	850 nm Diffusion IR nephelometry at 90°
•	Measure ranges : 0 to 4500 mg/L	5 to 4000 NTU in 5 ranges:
	Calibration:	• 5 - 50 NTU
	Range 0-500 mg/L according to NFEN872	• 5 - 200 NTU
	Range >500 mg/L according to NFT901052)	• 5 - 1000 NTU
		• 5 - 4000 NTU
		• AUTOMATIC
		Selected Automatically
•	Accuracy	<5% of the reading
•	Resolution	0.01 to 1NTU-mg/L
•	Temperature compensation	Via CTN
•	Storage Temperature (°C)	-10 to +60
•	Operation Temperature (°C)	0 to +50
•	Power Supply	Built-in Replaceable Lithium Battery
•	Rated Voltage (V)	3.6
•	Battery Lifetime	10,000+ transmissions
•	Materials	Sensor Head: PVC, DELRIN, Quartz, PMMA, Polyamide,
		cable: polyurethane, Enclosure: POM
•	Max Pressure on Sensor Head	5bar
•	Weight (g)	~850 (for 3m cable)
•	Protection Rate	IP68 for sensor head and
		IP66 and UV Protected enclosure
•	SIM Card Type	4FF Nano-SIM, from any Network Provider
•	Firmware Update	Over The Air, Locally via Wireless Connectivity
•	Sampling Period	Configurable via downlink (default 4 hours)
•	Communication Bands	B1/B2/B3/B4/B5/B8/B12/B13/B18/B19/B20/B26/B28 and B39
•	Antenna	Internal (Default)/ External
		(customised options available)



# Turbidity Monitoring in Remote Industrial Water Treatment Units

#### PLATFORM FEATURES

10Sorex's software platform is a comprehensive and user-friendly solution specifically designed for diesel delivery management. The platform offers a wide range of features tailored for diesel delivery operations, including real-time data visualization, customizable alerts and notifications, historical data analysis, and predictive analytics. It provides users with a holistic view of their diesel delivery assets, allowing them to make data-driven decisions for optimal fuel management. The platform is accessible via web browsers and mobile devices, providing convenient remote access to critical information anytime, anywhere. 10Sorex's software platform is designed with a user-centric approach, offering intuitive navigation and a user-friendly interface for easy setup and configuration. With its advanced features and ease of use, 10Sorex's software platform empowers users to effectively monitor and manage their diesel delivery operations in remote areas, ensuring efficient and sustainable fuel resource management.


- Encrypted ultra-low power communication protocol
- Advanced device inventory
- Integration APIs for enterprise systems
- Multi-tenant role-based access control
- Data export and import
- White-label platform for enterprise runs on private account
- Variable alarm setting for high and low thresholds and multi-channel alerting
- Sampling and transmission interval configuration
- Transmission condition configuration
- Other configurations and customization available on request








# Turbidity Monitoring in Remote Industrial Water Treatment Units
















## Turbidity Monitoring in Remote Industrial Water Treatment Units

#### **INTEGRATION OPTIONS**

10Sorex's solution sets itself apart with its pre-configured and plug-and-play design, eliminating the complexities of configuration, programming, and connection to the platform. This unique approach ensures that users can start monitoring their diesel tanks quickly and easily without any technical hassles. Additionally, 10Sorex offers seamless integratability at both the network and platform levels, allowing for easy integration with any network or visualization/analysis platform. This competitive advantage makes 10Sorex's solution highly adaptable and compatible with existing systems, providing users with flexibility and convenience in managing their diesel resources effectively.



## Turbidity Monitoring in Remote Industrial Water Treatment Units

#### **ORDERING PROCESS**

10Sorex offers simple and easy way to order the solution from any location on earth with narrow band cellular coverage. Please visit our sales portal (<a href="www.10sorex.com">www.10sorex.com</a>) or contact us to discuss your application. This is the first step to experience a reliable IoT solution at scale.



Purchase the solution online



Learn more about our Software Platform



View the Included Sensor Datasheet



Browse our other solutions

All details are subject to change without prior notice © All Rights Reserved for 10Sorex

Rev2025\_00

